

KIM



Composition 90% Polyester 10% Polyamide	Surface 86% Polyester 14% Polyamide	Base material 100% Polyester
Roll length 35 m	Width 142 cm +/- 2 cm	Usable width 140 cm +/- 2 cm
Weight / m2 395 g +/- 5%	Abrasion resistance DIN EN ISO 12947-1+2 85.000 T Category B	Pilling DIN EN ISO 12945-2 (2000 T) 4 Category B
Tensile strength DIN EN ISO 13934-1 Warp 1004 (37,4) Werft 585 (24,5) Category A / B	Tear growth resistance DIN EN ISO 13937-3 N Warp 68,0 Werft 143,7 Category A / A	Resistance to seam slippage DIN EN ISO 13936-2, 180 N Warp 2,3 mm Werft 2,0 mm Category A / A
Fastness to rubbing dry DIN EN ISO 105-X12 Bright colors 5 Dark colors 4 - 5 Category A / A	Fastness to rubbing wet DIN EN ISO 105-X12 Bright colors 4 - 5 Dark colors 4 Category A / A	Fastness to light DIN EN ISO B 02 >5 Category A

Item specification according to DIN EN 14465: 2006

All results were gathered from differenz samples and represent average inductive values.



CTL® GmbH
Chemisch-Technologisches Laboratorium



We are sponsoring member of Deutsche Gütegemeinschaft aft Möbel e.V. - Quality-assured furniture can be recognised by this quality mark.



REACH
Passed



AZO-Color
(\$35 LMBG B 82.02-2,3,3)
Passed

Cleaning instructions

