

PORTOFINO



Composition 80% Polyester 20% Polyurethane	Surface 100% Polyester	Base material 50% Polyester 50% Polyurethane
Roll length 30 m	Width 142 cm +/- 2 cm	Usable width 140 cm +/- 2 cm
Weight / m2 700 g +/- 5%	Abrasion resistance DIN EN ISO 12947-1+2 50.000 T Category B	Pilling DIN EN ISO 12945-2 (2000 T) 4 - 5 Category A
Tensile strength DIN EN ISO 13934-1 Warp 1216 (26,7) Werft 443 (20,6) Category A / B	Tear growth resistance DIN EN ISO 13937-3 N Warp 44,8 Werft 33,1 Category A / B	Resistance to seam slippage DIN EN ISO 13936-2, 180 N Warp 1,6 mm Werft 1,4 mm Category A / A
Fastness to rubbing dry DIN EN ISO 105-X12 Bright colors 4 Dark colors 4 Category B / B	Fastness to rubbing wet DIN EN ISO 105-X12 Bright colors 3 - 4 Dark colors 3 - 4 Category B / B	Fastness to light DIN EN ISO B 02 4 Category C

Item specification according to DIN EN 14465: 2006

All results were gathered from differenz samples and represent average inductive values.



CTL GmbH
Chemisch-Technologisches Laboratorium



We are sponsoring member of Deutsche Gütegemeinschaft aft Möbel e.V. - Quality-assured furniture can be recognised by this quality mark.



REACH
Passed



AZO-Color
(\$35 LMBG B 82.02-2,3,3)
Passed

Cleaning instructions

