

# SALT



<b>Composition</b> 100% Polyester	<b>Surface</b> 100% Polyester	<b>Base material</b> 100% Polyester
<b>Roll length</b> 35 m	<b>Width</b> 142 cm +/- 2 cm	<b>Usable width</b> 140 cm +/- 2 cm
<b>Weight / m2</b> 295 g +/- 5%	<b>Abrasion resistance</b> DIN EN ISO 12947-1+2 55.000 T Category B	<b>Pilling</b> DIN EN ISO 12945-2 (2000 T) 4 Category B
<b>Tensile strength</b> DIN EN ISO 13934-1 Warp 945 (28,6) Werft 499 (35,6) Category A / B	<b>Tear growth resistance</b> DIN EN ISO 13937-3 N Warp 75,4 Werft 63,5 Category A / A	<b>Resistance to seam slippage</b> DIN EN ISO 13936-2, 180 N Warp 3,0 mm Werft 2,2 mm Category A / A
<b>Fastness to rubbing dry</b> DIN EN ISO 105-X12 Bright colors 5 Dark colors 4 - 5 Category A / A	<b>Fastness to rubbing wet</b> DIN EN ISO 105-X12 Bright colors 4 - 5 Dark colors 4 - 5 Category A / A	<b>Fastness to light</b> DIN EN ISO B 02 5 Category B

Item specification according to DIN EN 14465: 2006

All results were gathered from differenz samples and represent average inductive values.



CTL® GmbH  
Chemisch-Technologisches Laboratorium



We are sponsoring member of Deutsche Gütegemeinschaft aft Möbel e.V. - Quality-assured furniture can be recognised by this quality mark.



**REACH**  
Passed



**AZO-Color**  
(\$35 LMBG B 82.02-2,3,3)  
Passed

**Cleaning instructions**

