

WAVE



Composition 64% Polyurethane 25% Polyester 11% Cotton	Surface 100% Polyurethane	Base material 70% Polyester 30% Cotton
Roll length 40 m	Thickness 0.80 mm	Width / Usable width 140 cm +/- 2 cm 138 cm +/- 2 cm
Weight / m2 375 g +/- 5%	Abrasion resistance DIN EN ISO 5470-2:2003-10, V1 >100.000 T Category A	Tensile strength DIN EN ISO 1421:2017-03, V1 Warp 655 (29,2) Werft 548 (15,8) Category A / A
Tear growth resistance DIN EN ISO 4674-1:2017-03, V A Warp 66,9 Werft 53,9 Category A / A	Resistance to seam slippage DIN EN ISO 13936-2, 180 N Warp 2,3 mm Werft 2,8 mm Category A / A	Flexibility resistance DIN EN ISO 32100:2003-11 100.000 Cycles Warp OK Werft OK Diagonal OK Category A / A
Fastness to rubbing dry and wet DIN EN ISO 105-X12 Bright colors 5 Dark colors 5 Category A / A	Coating adhesion DIN EN ISO 2411:2018-02 Warp 58,4 Werft 60,9 Category A / A	Fastness to light DIN EN ISO 105-B02:2014-11 V3 >5 Category A

Item specification according to DIN EN 15618: 2012

All results were gathered from differenz samples and represent average inductive values.



We are sponsoring member of Deutsche Gütegemeinschaft Möbel e.V. - Quality-assured furniture can be recognised by this quality mark.



REACH
Passed



AZO-Color
(\$35 LMBG B 82.02-2,3,3)
Passed

Cleaning instructions

