

Bari



Composition

100% recycled Polyester

Surface

100% recycled Polyester

Base Material

100% recycled Polyester

Roll length

approx. 40 m

Width

142 cm +/- 2 cm

Usable width

140 cm +/- 2 cm

Weight / m2

320 g +/- 5%

Abrasion resistance

DIN EN ISO 12947-1+2
70.000 T
Category B

Pilling

DIN EN ISO 12945-2 (2000 T)
4-5
Category A

Tensile strength

DIN EN ISO 13934-1
Warp 1450 (29,0)
Werft 1260 (27,7)
Category A / A

Tear growth resistance

DIN EN ISO 13937-3 N
Warp 163,1
Werft 146,7
Category A / A

Resistance to seam slippage

DIN EN ISO 13936-2, 180 N
Warp 2,0 mm
Werft 2,2 mm
Category A / A

Fastness to rubbing dry

DIN EN ISO 105-X12
Bright colors 4-5
Dark colors 4
Category A / A

Fastness to rubbing wet

DIN EN ISO 105-X12
Bright colors 4-5
Dark colors 4
Category A / A

Fastness to light

DIN EN ISO B 02
5
Category B

Item specification according to DIN EN 14465: 2006

All results were gathered from differenz samples and represent average indicative values.



CTL® GmbH
Chemisch-Technologisches Laboratorium



STANDARD
100



ZH015 182853
TESTEX



We are a
supporting
member of the
Deutsche
Gütegemeinschaft
Möbel e.V.
(German Furniture
Quality
Association).
Quality-assured
furniture can be
identified by this
quality mark.



REACH
Passed



AZO-Color
(\$35 LMBG B 82.02-2,3,3)
Passed

Cleaning instructions

