

CAPRI



Composition 100% Polyester	Surface 100% Polyester	Base material 100% Polyester
Roll length approx. 40 m	Width 142 cm +/- 2 cm	Usable width 140 cm +/- 2 cm
Weight / m2 340 g +/- 5%	Abrasion resistance DIN EN ISO 12947-1+2 >100.000 T Category A	Pilling DIN EN ISO 12945-2 (2000 T) 4 Category B
Tensile strength DIN EN ISO 13934-1 Warp 1439 (40,0) Werft 986 (34,4) Category A / A	Tear growth resistance DIN EN ISO 13937-3 N Warp 68,7 Werft 54,4 Category A / A	Resistance to seam slippage DIN EN ISO 13936-2, 180 N Warp 1,8 mm Werft 1,7 mm Category A / A
Fastness to rubbing dry DIN EN ISO 105-X12 Bright colors 4 - 5 Dark colors 4 - 5 Category A / A	Fastness to rubbing wet DIN EN ISO 105-X12 Bright colors 3 - 4 Dark colors 3 - 4 Category A / A	Fastness to light DIN EN ISO B 02 4 - 5 Category B

Item specification according to DIN EN 14465: 2006

All results were gathered from differenz samples and represent average indicative values.



CTL® GmbH
Chemisch-Technologisches Laboratorium



STANDARD 100
ZH015 182853
TESTEX



We are a supporting member of the Deutsche Gütegemeinschaft Möbel e.V.

Quality-assured furniture can be recognised by this quality mark: Our furniture supply products marked with Golden M meet the technical requirements of the RAL-GZ 430 quality and testing regulations



REACH
Passed



AZO-Color
(\$35 LMBG B 82.02-2.3.3)
Passed

Cleaning instructions

