

COMO



Composition 100% Polyester	Surface 100% Polyester	Base Material 100% Polyester
Roll length approx. 40 m	Width 142 cm +/- 2 cm	Usable width 140 cm +/- 2 cm
Weight / m2 455 g +/- 5%	Abrasion Resistance DIN EN ISO 12947-1+2 >100.000 T Category A	Pilling DIN EN ISO 12945-2 (2000 T) 4 Category B
Tensile Strength DIN EN ISO 13934-1 Warp 1418 (32,5) Werft 785 (23,6) Category A / A	Tear growth resistance DIN EN ISO 13937-3 N Warp 167,10 Werft 117,90 Category A / A	Resistance to seam slippage DIN EN ISO 13936-2, 180 N Warp 2,3 mm Werft 3,2 mm Category A / A
Fastness to rubbing dry DIN EN ISO 105-X12 Bright colors 5 Dark colors 4 - 5 Category A / A	Fastness to rubbing wet DIN EN ISO 105-X12 Bright colors 4 - 5 Dark colors 4 Category A / A	Fastness to light DIN EN ISO B 02 5 Category B

Item specification according to DIN EN 14465: 2006

All results were gathered from differenz samples and represent average indicative values.



REACH
Passed



AZO-Color
(\$35 LMBG B 82.02-2,3,3)
Passed

Cleaning instructions

