

# TIVOLI



|                                                                                                            |                                                                                                            |                                                                                                             |
|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>Composition</b><br>100% Polyester                                                                       | <b>Surface</b><br>100% Polyester                                                                           | <b>Base material</b><br>100% Polyester                                                                      |
| <b>Roll length</b><br>approx. 40m                                                                          | <b>Width</b><br>142 cm +/- 2 cm                                                                            | <b>Usable width</b><br>140 cm +/- 2 cm                                                                      |
| <b>Weight / m2</b><br>260 g +/- 5%                                                                         | <b>Abrasion resistance</b><br>DIN EN ISO 12947-1+2<br>60.000 T<br>Category A                               | <b>Pilling</b><br>DIN EN ISO 12945-2 (2000 T)<br>4-5<br>Category A                                          |
| <b>Tensile strength</b><br>DIN EN ISO 13934-1<br>Warp 1499 (54,60)<br>Weft 914 (30,90)<br>Category A/A     | <b>Tear growth resistance</b><br>DIN EN ISO 13937-3 N<br>Warp 153,10<br>Weft 143,70<br>Category A/A        | <b>Resistance to seam slippage</b><br>DIN EN ISO 13936-2, 180 N<br>Warp 2,0mm<br>Weft 3,8mm<br>Category A/A |
| <b>Fastness to rubbing dry</b><br>DIN EN ISO 105-X12<br>Bright colors 5<br>Dark colors 4-5<br>Category A/A | <b>Fastness to rubbing wet</b><br>DIN EN ISO 105-X12<br>Bright colors 4-5<br>Dark colors 4<br>Category A/A | <b>Fastness to light</b><br>DIN EN ISO B 02<br>4<br>Category B                                              |

Item specification according to DIN EN 14465: 2006

All results were gathered from differenz samples and represent average indicative values.



**REACH**  
Passed



**AZO-Color**  
(\$35 LMBG B 82.02-2,3,3)  
Passed

## Cleaning instructions

