

VIGO



Composition

8,6% Linen – 28,5% Viscose –
14,9% Cotton – 48% Polyester

Surface

8,6% Linen – 28,5% Viscose –
14,9% Cotton – 48% Polyester

Base material

Roll length

25-30m

Width

140cm

Usable width

138cm

Weight / m2

545g/m2

Abrasion resistance

DIN EN ISO 12947-1+2
>25.000
Category

Pilling

DIN EN ISO 12945-2 (2000 T)
4-5
Category

Tensile strength

DIN EN ISO 13934-1
Warp >350N
Weft >350N
Category

Tear growth resistance

DIN EN ISO 13937-3 N
Warp >25N
Weft >25N
Category

Resistance to seam slippage

DIN EN ISO 13936-2, 180 N
Warp <4mm
Weft <4mm
Category

Fastness to rubbing dry

DIN EN ISO 105-X12
Light colors 4-5
Dark colors 4
Category

Fastness to rubbing wet

DIN EN ISO 105-X12
Light colors 4
Dark colors 3-4
Category

Fastness to light

DIN EN ISO B 02
5
Category

Item specification according to DIN EN 14465: 2006

If results were gathered from differenz samples and represent average inductive values.



CTL® GmbH
Chemisch-Technologisches Laboratorium



We are a supporting member of
the Deutsche Gütegemeinschaft
Möbel e.V.

Quality-assured furniture can be
recognised by this quality mark:
Our furniture supply products
marked with Golden M meet the
technical requirements of the
RAL-GZ 430 quality and testing
regulations



REACH
Passed



AZO-Color
(§35 LMBG B 82.02-2,3,3)
Passed

Cleaning instructions

